



Sentryglas® ionoplast interlayer provides safer, stronger, more durable glass railing system for Kirby Drive Tower in Texas



The frameless glass railing system installed at 2727 Kirby Drive, a 30-storey luxury condominium tower block in Houston, Texas. 143 balconies were retrofitted with C.R. Laurence's patented CRL L56S Series TAPER-LOC® Glass Railing System and SentryGlas® ionoplast interlayers.

The glass railing construction used on the balconies and pool deck railings, which were designed by architects CDC Curtainwall Design Corporation, comprise a 14 mm (9/16") tempered laminated glazing that uses SentryGlas® 1.52 mm (0.60") thickness interlayer supplied in 6 mm tempered x 1.52 mm x 6 mm (½" x 0.60" x ½") tempered glass makeup. These were fitted to CRL-Blumcraft 324 series Top Rail, custom powder coated with Newlar El Cajon Silver. In total, more than 1,067 meters (3500 linear feet) of glass railing systems were retrofitted to 143 balconies.


For this project, SentryGlas® ionoplast interlayer was specified by CDC Curtainwall Design Corp. and C.R. Laurence Co. (CRL), a leading global manufacturer and supplier to the glazing, architectural, railing, construction, industrial and automotive industries. CRL's L56S Series TAPER-LOC® Glass Railing System was also specified for this application. This system is based on

CRL's patented TAPER-LOC® X System, a completely dry glazed system for securing glass panels into the base shoe. This system requires no messy expansion cement, is 50 percent faster to install compared to traditional systems, and does not affect the performance of the laminate interlayer.

According to Chris Hanstad, brand manager at CRL: "Our goal here is to build railing systems that are safer, stronger but still offer brilliant transparency. We selected SentryGlas® because it was found to be safer and stronger than alternative laminates and is also extremely clear, which means residents get virtually crystal clear, unobstructed views from their balcony. Kirby Drive is a luxury apartment building; so aesthetics also were very important. SentryGlas® offers excellent weathering durability with no discoloration, creep or delamination issues."



Sentryglas® ionoplast interlayer provides safer, stronger, more durable glass railing system for Kirby Drive Tower in Texas



SentryGlas® is more than 100 times stiffer and 50 percent stronger than PVB alternatives. Due to the strength of the interlayer, SentryGlas® demonstrate excellent postglass-breakage performance. Upon impact, the glass may break, but dangerous fragments will adhere to the SentryGlas® interlayer, reducing the risk of injury to people in the vicinity.

Lighter façade panels enable more subtle supporting structures

For decades, interlayers made of polyvinyl butyral (PVB) have been the industry standard when producing laminated safety glass. Architects are well aware of the possibilities and limitations of such glass when used extensively in façade engineering, for roofing and window panels. In contrast, SentryGlas® enables an entirely new approach because the interlayer is over 100 times stiffer and five times stronger than PVB. As a consequence, there is an almost perfect transmission of load between two laminated sheets of glass, even at high temperatures, leading to the excellent flexural behavior of the glass when under load - also under direct sunlight in high summer. Accordingly, laminates with SentryGlas® show less than half the rate of deflection when compared to laminates with PVB, when under the same load, and thus almost the same behavior as monolithic glass of the same thickness.





CRL's 200 Series ARS Aluminum Railing System was retrofitted to the pool deck areas at Kirby Drive. SentryGlas® was chosen because it is safer and stronger than alternative laminates and is extremely clear, giving residents virtually crystal clear, unobstructed views from their balconies. SentryGlas® also offers excellent weathering durability with no discolouration, creep or delamination issues.



Sentryglas® ionoplast interlayer provides safer, stronger, more durable glass railing system for Kirby Drive Tower in Texas



As well as improved strength and stiffness, other benefits of SentryGlas® include:

- Safety: In the event of breakage, glass fragments remain firmly bonded to the interlayer, reducing the chance for injury
- Security: SentryGlas® can be used in glazing that withstands bullets, hurricane-force winds and even bomb blasts
- **Durability:** SentryGlas® is extremely durable and resistant to clouding, even after years of exposure
- Design Versatility: SentryGlas® can be used in glass manufactured flat or curved, including annealed, toughened, heat-strengthened, spandrel, wired, patterned and color tinted glass
- UV control: SentryGlas® is available with or without UV transmittance

INFORMATION PROVIDED BY:

Chris Hanstad, Brand Manager, C.R Laurence Company, Inc. Tel.: 001-323-588-1281, Fax: 001-323-584-5289

chris_hanstad@crlaurence.com, www.crlaurence.com

REGIONAL CONTACT CENTERS

Kuraray Co., LTD Ote Center Bldg. 1-1-3, Otemachi Chiyoda-ku, Tokyo, 100-8115, Japan Phone: +81 3 6701 1508

Kuraray Europe GmbH Glass Laminating Solutions Philipp-Reis-Str. 4 65795 Hattersheim, Germany Phone: +49 (0) 69 30585300

Kuraray Americas, Inc. 2625 Bay Area Blvd. #600 Houston TX 77058, USA Phone: +1.800.423.9762

Kuraray Mexico S.de R.L. de C.V. Homero 206, Polanco V seccion, cp 11570, Mexico City, Mexico Phone: +52 55 5722 1043

For further information about SentryGlas®, please visit www.sentryglas.com



Copyright ©2014 Kuraray. All rights reserved. Photos: C.R. Laurence Co.

SentryGlas® is a registered trademark of E. I. du Pont de Nemours and Company or its affiliates for its brand of interlayers. It is used under license by Kuraray. TAPER-LOC® is a registered trademark of C.R. Laurence.

The information provided herein corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials or additives or in any process, unless expressly indicated otherwise. The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since Kuraray cannot anticipate all variations in actual end-use conditions, Kuraray make no warranties and assume no liability in connection with any use of this information. Nothing in this publication is to be considered as a license to operate under a recommendation to infringe any patent rights. Document Ref. GLS-LGN-2012-12